

LEGEND


EXISTING WALL TO REMAIN	
NEW WALL	
CONCRETE TOPPING SEE NOTE 1	

CONSTRUCTION KEY

- PROVIDE 8" X 8" SWING OPEN ACCESS PANELS AT 3'-0" AFF. TO CENTER OF PANEL.
- PROVIDE CONCRETE RAMP SLOPE 1:20 MIN.
- GRADUAL SLOPE OF CONCRETE TO RAMP. (ELIMINATE TRIPPING HAZARD)

NOTE:

1. IN ALL ROOMS DESIGNATED AS +2' ELEV. - SHOTBLAST EXISTING CONCRETE SLAB AND PROVIDE 2" CONCRETE TOPPING. (AREA SHOWN AS SHADED) COORDINATE WITH TRACK INSTALLATION. PLACE CONCRETE IN RECTANGULAR SECTIONS WITH LENGTH TO WIDTH RATIO NOT TO EXCEED 2:1
2. SEE ELEVATIONS (A-200 & A-201) FOR WORK ON EXTERIOR WALLS.
3. SEE DRAWINGS A-111 & A-112 FOR LINTELS OVER DUCT PENETRATIONS THROUGH INTERIOR CMU WALLS.
4. SEE DRAWING A-500 FOR PARTITION TYPES.
5. SEE DRAWING A-501 FOR LINTEL DETAILS OVER DOORS AND DOOR SCHEDULE/TYPES.



1 FIRST FLOOR PLAN

SCALE: 1/16"=1'-0"

B JAMB & LINTEL DETAIL

SCALE: 1 1/2"=1'-0"

A JAMB & LINTEL DETAIL

SCALE: 1 1/2"=1'-0"